


BS Series



select	Inquiry	Designation		Principal dimensions (mm)			Basic load ratings (kN)		Limiting Speed	Weight (kg)
		Cylindrical Bore	Taper Bore	d	D	B	Dyn Cr	Stc Cor		
BS2-2217-2CS	BS2-2217-2CSK	85	150	44	285	325	1100	3,00		
BS2-2218-2CS	BS2-2218-2CSK	90	160	48	325	375	1000	3,70		
BS2-2220-2CS	-	100	180	55	425	490	900	5,50		
BS2-2224-2CS	-	120	215	69	630	765	750	9,75		
BS2-2315-2CS	-	75	160	64	440	475	950	6,54		
BS2-2216-2CS	BS2-2216-2CSK	80	140	40	236	270	1200	2,40		
BS2-2213-2CS	BS2-2213-2CSK	65	120	38	193	216	1500	1,60		
BS2-2214-2CS	BS2-2214-2CSK	70	125	38	208	228	1400	1,80		
BS2-2215-2CS	BS2-2215-2CSK	75	130	38	212	240	1300	2,10		
BS2-2211-2CS	BS2-2211-2CSK	55	100	31	125	127	1700	1,00		
BS2-2212-2CS	BS2-2212-2CSK	60	110	34	156	166	1600	1,30		
BS2-2207-2CS	-	35	72	28	86,5	85	2400	0,52		
BS2-2208-2CS	BS2-2208-2CSK	40	80	28	96,5	90	2200	0,57		
BS2-2209-2CS	BS2-2209-2CSK	45	85	28	102	98	2000	0,66		
BS2-2210-2CS	B52-2210-2CSK	50	90	28	104	108	1900	0,70		
BS2-2206-2CS	-	30	62	25	64	60	2800	0,34		